

FUSO SHOGUN

Shogun FV70 6X4 - MY21

10.7L / AMT / MECH SUSP. / MWB



OUR SAFEST AND CLEANEST SHOGUN YET. THE MY21 SHOGUN IS EQUIPPED WITH ABA5, PD, LDWS, ESP, AAA, IHC, DRL AND A EURO VI STEP D ENGINE. ALL BACKED BY OUR CLASS LEADING SERVICE INTERVALS AND 5 YEAR WARRANTY.

GVM

25,400_{KG}

GCM

53,000_{KG}

Power/Torque

290_{KW} / 2000_{NM}

335_{KW} / 2200_{NM}

- Heavy rigid licence required
- Actual vehicle may differ from above image

SHOGUN SPECIFICATIONS

MODEL

A	6X4 FV70 395HP STEEL SUSP. MWB 12 SP. AMT FV70HK2VFAA-MY21
B	6X4 FV70 455HP STEEL SUSP. MWB 12 SP. AMT FV70HK4VFAA-MY21

WHEEL BASE

4300mm
4300mm

GVM


25,400kg
25,400kg

GCM

53,000kg
53,000kg

Engine

Engine Version	A FUSO OM470-T2 Diesel	B FUSO OM470-T4 Diesel
Configuration	6 Cyl. In-line OHV	
Injection System	Common Rail Direct Injection with Pressure Booster	
Type	Asymmetric Turbocharger, Air to Air Intercooler	
Displacement	10.7 litre (10677 cc)	
Bore	125 mm	
Stroke	145 mm	
Power (DIN)	A 290 kW (395 hp) @ 1600 rpm	B 335 kW (455 hp) @ 1600 rpm
Torque (DIN)	A 2000 Nm (1475 lb.ft) @ 1100 rpm	B 2200 Nm (1622 lb.ft) @ 1100 rpm
Maximum Engine Speed	2100 rpm	
Compression Ratio	18.5:1	
Air Cleaner	Paper Element Type with Restrictor Indicator. Vertical Intake Mounted on Clean Air Side (RH)	
Emission Control	Diesel Particulate Filter (DPF) plus SCR After-Treatment System	
Emission Level	ADR 80/04 - Euro VI	



Fuel

Tank Type	Rectangular Aluminium Tank with Locking Cap
Fuel Capacity *	400 Litres
Filtration	Filter with Water Separator and Dash Indicator
AdBlue Exhaust Fluid Capacity	60 Litres, Tank fitted with locking AdBlue cap
Speed Limiter	Speed Limited 100km/h
Notes	*Max Fill to approx 95% of capacity

Cooling

Fan Drive	Electronically controlled (Viscous)
Radiator	Corrugated Fin with Expansion Tank

Electrical

Voltage	24V Negative Ground
Battery Capacity	2x12V, 150Ah/20hr
Battery Specification	2x145G51 (N150)
Headlamp Type	Automatic Type Low Beam: LED High Beam: Halogen
Fog Light	Halogen
Daytime Running Lamps	LED

Clutch

Clutch Model	FUSO K4/430
Type	Single Dry Plate
Operation/Specification	Automated Manual (no clutch pedal)

Transmission

Version	FUSO Automated Manual G230-12
Type/Speeds	12 Speed Automated Manual with Auto, Economy and Manual Modes
Features	Crawler Mode Skip Shift Function for Light Loads ECO Mode to Minimise Fuel Usage
Ratios	1st: 11.672 2nd: 9.101 3rd: 7.055 4th: 5.501 5th: 4.400 6th: 3.430 7th: 2.652 8th: 2.068 9th: 1.603 10th: 1.250 11th: 1.000 12th: 0.779 RHigh: 9.101 RLow: 11.672 Torque limited from 1st to 3rd and Reverse
PTO Opening	Rear of Transmission

Propeller Shaft

Type	Single Main Shaft GW5E2200 Inter-axle Shaft P12
------	--

Front Axle

Axle Version	FUSO F900T
Type	Reverse Elliot 'I' Beam
Capacity *	7100kg
Notes	*See MAX LOADING for vehicle capacity.

Front Suspension

Type	Long Taper Leaf with Stabiliser Bar and Double Acting Shock Absorbers
Size	1500x90mm Leaves

Rear Axle

Type	Full Floating Hypoid Type Tandem Drive with differential cross locks between front & rear tandem axles Optional-Limited Slip Differential LSD on both axles.
Axle Version	FUSO R10TT/R10T
Capacity*	21600kg
Ratio	4.625:1
Notes	*See MAX LOADING for vehicle capacities

Rear Suspension

Type	Mechanical Suspension
Details	Long Leaf Taper, 6 Rod Trunnion
Size Main Leaves	1320x90mm

Max Loading

Front	6500kg
Rear	21600kg
Total	25400kg

SHOGUN SPECIFICATIONS

MODEL		WHEEL BASE	GVM	GCM
A	6X4 FV70 395HP STEEL SUSP. MWB 12 SP. AMT FV70HK2VFAA-MY21	4300mm	25,400kg	53,000kg
B	6X4 FV70 455HP STEEL SUSP. MWB 12 SP. AMT FV70HK4VFAA-MY21	4300mm	25,400kg	53,000kg

Options		
Options	A	B
	Q48: - Limited Slip Differential - LSD	Q51: - Limited Slip Differential - LSD
	Q49: - Limited Slip Differential - LSD - Engine Flywheel PTO 650N	Q52: - Limited Slip Differential - LSD - Engine Flywheel PTO 650N
Steering		
Type	Integral Ball and Nut	
Steering Column	Tilt/Telescopic Adjustable	
Brakes		
Type	Full Air, Dual Circuit with FUSO Taper Rollers	
Size Front	410x160mm	
Size Rear	410x200mm	
Features	Brake Priority System	
Park Brake	Rear Wheel Spring Actuated	
Engine	Jacobs Brake	
	3 Levels of Retardation	
Trailer	Hand Control Valve, Air Lines	
	Coupling and Electrical Cable	
Wheels & Tyres		
Wheel Type	10, Single Piece Alloy Disc	
Wheel Size	22.5x8.25	
Wheel Stud Pattern	10x335mm PCD	
Tyre Brand	Bridgestone	
Tyre Size Front	295/80R22.5 152/148	
Tyre Size Rear	11R22.5 148/145	
Chassis		
Type	Reinforced Parallel Channel	
Size	300x90x7.0 mm	
Width	840 mm	
Tensile Strength	540 MPa	

Instruments	
Gauges	Speedometer Tachometer Fuel Level Air Pressure AdBlue Level
Colour Information Display	Odometer Tripmeter (x2) Hour Meter (x2) Outside Temperature AdBlue Level DPF Information Driving Range (Fuel and AdBlue) Current Vehicle Speed Cruise Control Lane Departure Warning Active Attention Assist Warning Alarm Clock Level Control Service Indicator & Reminder System Air Pressure Coolant Temperature Engine Oil Level & Running Time
Warning Lamps	ABS ASR ESP ESP Off Turn Signal Headlamps High Beam Hill Holder Auxiliary Brake Parking Brake Engine Over-speed Air Pressure Low Height Control Cab Tilt Lock DPF Regeneration DPF Status AdBlue Empty AdBlue Contamination Active Brake Assist
Warning Lamp/Buzzer	Air Pressure Cab Tilt Engine Over-speed AdBlue Empty AdBlue Contamination
Multi-Media Package	
Satellite Navigation	GPS navigation specifically designed for commercial vehicle applications, with 3 years of Map updates included.
Colour Display	7 inch LCD with touch screen control
Phone Connectivity	Bluetooth® hands free
Audio Visual Entertainment	Bluetooth® music streaming compatible Digital radio DAB+ (also AM/FM for areas not covered by DAB+) & USB
Camera Compatibility	Reverse camera (Factory Fitted) + 5 additional camera options #
Notes	# Cameras available through spare parts

SHOGUN SPECIFICATIONS

MODEL

A	6X4 FV70 395HP STEEL SUSP. MWB 12 SP. AMT FV70HK2VFAA-MY21
B	6X4 FV70 455HP STEEL SUSP. MWB 12 SP. AMT FV70HK4VFAA-MY21

WHEEL BASE

4300mm
4300mm

GVM

25,400kg
25,400kg

GCM


53,000kg
53,000kg

Standard Features		Mass estimated*	
Cruise Control	Adaptive with Stop and Go	Front*	A 4323kg B 4363kg
Hill Start System	Yes	Rear*	A 3347kg B 3342kg
Cab Cooling & Heating	Climate Control	Total*	A 7670kg B 7705kg
Accessory Power	24V Accessory Power Outlet (x2) plus Cigar Lighter	Notes	* Mass (est.) includes oil and water but excludes spare wheel, tools & fuel. Weights provided are subject to 3.5% variation (+/-)
Driving	Suspended Driver's Seat Central Locking Electric Windows LH Transom Window Opening Rear Quarter Glass Cup Holder Fluorescent Cabin Lamp Trailer Package including Trailer 'Stretch Brake'	Dimensions mm	
Storage	Centre Storage Compartments (x3 Total, Lockable x1) Driver's Overhead Storage Door Storage Pockets Coat Hooks	WFF (Width Front Fender) (mm)	2490
Cab: External	Fog Lights Door Side Impact Beams Roof Mounting Points max. static load 70kg Front End-Outline Marker Lamps External PTO controls	WRA (Width Rear Axle) (mm)	2475
Chassis	Integrated Front Underrun System (FUPS) Reverse Warning Buzzer Clear Top of Chassis Rail for ease of Body Fitment	WFT (Width Front Track) (mm)	2075
Active Safety		WRT (Width Rear Track) (mm)	1865
Safety Systems	ABA5 - Active Brake Assist 5 PD - Pedestrian Detection AAA - Active Attention Assist PCA - Proximity Control Assist Cruise Control LDWS - Lane Departure Warning System ESP - Electronic Stability Program ABS - Anti-lock Braking System ASR - Anti Slip Regulator LED Headlamps DRL - Daytime Running Lamps IHC - Intelligent Headlight Control	Width Frame (mm)	840
Reverse Warning	Wide Dynamic Range Camera and Buzzer	A - Length Overall (mm)	7640
Notes	Active Safety Systems primary function is to provide driver assistance to increase road safety in events of driver inattentiveness. These systems do not allow for lack of attention whilst driving and should not replace safe and alert driving.	B - Extreme Axle Spacing (mm)	4960
Passive Safety		C - Front Overhang (mm)	1370
Airbags	SRS Airbag - Driver	D - Wheelbase (mm)	4300
Body Strength	ECE-R29 Cab Strength Compliant	F - Rear Axle Spacing (mm)	1320
Seat Belts - Driver & Driver Assistant	3 Point ELR Lap Sash, Driver Pre-Tensioner.	G - Front Axle to Rear of Cab (mm)	700
Service Intervals		H - Rear of Cab to Rearmost Item Behind Cab (mm)	145
Interval*	50,000km or 12 Months (whichever occurs first)	I - Rearmost Item Behind Cab to Rear Axle (mm)	3455
Warranty*		J - Frame, Rear Axle to End (mm)	1970
Basic/Powertrain	5 Years or 500,000kms (whichever occurs first)	N - Height Overall (mm)	3300
Cab Perforation/Anti Corrosion	5 Years	O - Air Intake to Cab Roof (mm)	205
Notes	* Please refer to Fuso Owners Warranty Booklet for additional terms and conditions.	P - Height Cab to Ground (mm)	3095
Performance		Q - Height Cab to Frame (mm)	2090
Turning Circle (kerb to kerb - metres)	15.2	R - Height Rear Frame to Ground (mm)	1058
Electronically Speed Limited to:	100km/hr Conforms to ADR65/00	Body Builder's Notes	
Engine Speed (rpm) at 100km/hr (top gear)	1879	Notes	Chassis reinforcement must be utilised for Tipper/ Demountable type body configurations. To conform with ADR 13/00 (lighting requirements) the following must be adhered to at body installation. - If other than a flat type or tipper body is fitted, rear end out-line marker lamps must be installed. - If overall length exceeds 6.0 metres, side reflectors must be installed. - If overall length exceeds 7.5 metres, side marker lamps must be installed. To conform with ADR 42/04 (General Safety), rear wheel guards must be fitted to the vehicle.
Gradeability at Rated GVM (theoretical)*	A 61% B 66%		
Gradeability at Rated GCM (theoretical)*	28.5%		
Notes	*This is theoretical performance only. Actual performance may vary under different conditions		

SHOGUN SPECIFICATIONS

MODEL	
A	6X4 FV70 395HP STEEL SUSP. MWB 12 SP. AMT FV70HK2VFAA-MY21
B	6X4 FV70 455HP STEEL SUSP. MWB 12 SP. AMT FV70HK4VFAA-MY21

WHEEL BASE	GVM	GCM
4300mm	25,400kg	53,000kg
4300mm	25,400kg	53,000kg



Call 1800 033 557

or visit fuso.com.au

Unless specified in writing herein the accessories, applications, bodies or equipment depicted in this are for illustration purposes only and may not be available from Daimler Truck Australia Pacific Pty Ltd. ABN 86 618 413 282 DTAuP. No representation or warranty whatsoever is given in relation to any accessories, applications, bodies or equipment or suitability of same that are shown herein that may be manufactured, supplied or fitted by a party other than DTAuP. DTAuP reserves the right without notice or obligation to discontinue or make changes to the colour, designs, materials and specifications of the products and options referred to herein at any time. For the most current information and in order to ascertain which accessories, applications, bodies and equipment are available from DTAuP please contact your authorised FUSO dealer. Fuso is a registered trademark of Daimler Truck Australia Pacific Pty Ltd. Copyright DTAuP. Reproduction in whole or part prohibited without written approval. Valid from 12-Aug-21.