

# FUSO

# CANTER

## CANTER 815 TIPPER

4X2 / LSD / MANUAL OR DUONIC DCT



**OUR SAFEST CANTER EVER WITH AEBS, LDWS AND ESP STANDARD.**  
**CLASS LEADING 30,000KM SERVICE INTERVALS.**  
**ONLY JAPANESE FACTORY TIPPER WITH A LIMITED SLIP DIFFERENTIAL.**

**GVM**

**7,500<sub>KG</sub>**

**GCM**

**11,000<sub>KG</sub>**

**Power/Torque**

**110<sub>kW</sub> / 370<sub>Nm</sub>**

- Light rigid licence required. Can be derated and driven with a passenger car licence.
- Actual product may vary from image shown.

# CANTER SPECIFICATIONS

## MODEL

A	4X2 815 WIDE CAB TIPPER SWB 6 SP. DUONIC AMT (FEC81CR3SFBG)
B	4X2 815 WIDE CAB TIPPER SWB 5 SP. MAN (FEC81CR4SFBG)

## WHEEL BASE

2800mm
2800mm

## GVM (optional)


7,500kg (4,495kg)
7,500kg (4,495kg)

## GCM (optional)

11,000kg (7,995kg)
11,000kg (7,995kg)

### Engine

Engine Version	FUSO 4P10-T4 Diesel
Configuration	4 Cyl. In-line DOHC, 4-Valve
Injection System	Bosch Common Rail Direct Injection Bosch Piezo Technology Injectors
Type	Variable Geometry Turbo Charged Air to Air Intercooled
Displacement	3 litre (2998cc)
Bore	95.8mm
Stroke	104mm
Power (DIN)	110kW @ 2840~3500 rpm
Torque (DIN)	370Nm @ 1350~2840 rpm
Maximum Engine Speed	4100 rpm
Compression Ratio	17.5:1
Cooling System / Oil Cooler	Water cooled, 13.7L capacity/ Plate type engine oil cooler
Air Cleaner	Paper Element Type with Restrictor Indicator. Vertical Intake Mounted on Clean Air Side (RH)
Emission Control	Diesel Particulate Filter (DPF) Exhaust Dash Display DPF Status 0~9 (Empty~Full) Parked Regeneration possible from 7~9
Emission Level	ADR 80/03 - Euro 5



### Fuel

Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity *	100 Litres
Filtration	Filter with Water Separator and Indicator Sensor
Notes	*Max Fill to approx 95% of capacity

### Cooling

Fan Drive	Thermo modulated continuous control (Viscous)
Radiator	Corrugated Fin with Expansion Tank

### Electrical

Voltage	12V Negative Earth
Battery Capacity	2x12V, 70Ah/5hr
Battery Specification	115D31L x2
Headlamp Type	LED
Body Builder Harness	Yes

### Clutch

Clutch Model	A Fully Automated Dual Clutch (no clutch pedal)	B FUSO C4W30
Type	A Dual Clutch (Wet Multi-plate)	B Single Dry Plate, Direct Hydraulic Type

### Transmission

Version	A FUSO DUONIC M038S6	B FUSO M038S5
Type/Speeds	A 6 Speed Dual Clutch with Auto and Manual Modes	B 5 Speed with In-Dash Gearshift Lever
Features	A Virtually Instant Gear Changes In-Dash Gear Lever with Park Brake Position ECO Mode to Minimise Fuel Usage	B Synchronesh 1st-5th
Ratios	A 1st: 5.397 2nd: 3.788 3rd: 2.310 4th: 1.474 5th: 1.000 6th: 0.701 Rev. 5.397	B 1st: 5.494 2nd: 3.038 3rd: 1.592 4th: 1.000 5th: 0.723 Rev. 5.494

### Front Axle

Axle Version	FUSO F350T
Type	Reverse Elliot 'I' Beam
Capacity *	3100kg
Notes	*See MAX LOADING for vehicle capacity.

### Front Suspension

Type	Multi-Leaf with Double Acting Shock Absorbers
Size	1150x70mm Leaves

### Rear Axle

Type	Full Floating Banjo Type with Positive Locking Limited Slip Differential (LSD).	
Axle Version	FUSO R035T	
Capacity*	6000kg	
Ratio	A 5.714:1	B 5.285:1
Notes	*See MAX LOADING for vehicle capacity.	

### Rear Suspension

Type	Steel Suspension
Details	Semi-Elliptic Leaf with Double Acting Shock Absorbers
Size Main Leaves	1250x70mm
Size Helper Leaves	880x70mm

### Max Loading

Front	3100kg
Rear	6000kg
Total	7500kg

### Options

Options	H31: 4495/7995kg GVM/GCM Rating
---------	---------------------------------

### Steering

Type	Integral Ball and Nut Type
Steering Column	Tilt/Telescopic Adjustable
Power Assist	Standard

# CANTER SPECIFICATIONS

## MODEL

A	4X2 815 WIDE CAB TIPPER SWB 6 SP. DUONIC AMT (FEC81CR3SFBG)
B	4X2 815 WIDE CAB TIPPER SWB 5 SP. MAN (FEC81CR4SFBG)

## WHEEL BASE

2800mm
2800mm

## GVM (optional)

7,500kg (4,495kg)
7,500kg (4,495kg)

## GCM (optional)

11,000kg (7,995kg)
11,000kg (7,995kg)

Brakes		Standard Features	
Type	Hydraulic Dual Circuit with Front and Rear Discs Twin Calliper Front and Rear	Airbag(s)	Dual Air Bags and Seat Belt Pre-Tensioners (Driver & Far Side Passenger)
Size Front	252x40mm	Active Safety Features	ABS plus Electronic Brake force Distribution (EBD) Advanced Emergency Braking (AEBS) Anti-Slip Regulator (ASR) Electronic Stability Program (ESP) Lane Departure Warning System (LDWS)
Size Rear	252x40mm	Cruise Control	A Yes B No
Features	ABS plus EBD (Electronic Brake Distribution) Active Emergency Braking System (AEBS) Electronic Stability Program (ESP) Exhaust Brake Electronic Brake Wear Sensors	Hill Start System	A Yes B No
Park Brake	Transmission Mounted	Cab Cooling & Heating	Air Conditioner / Heater / Demister
Wheels & Tyres		Accessory Power	12V Accessory Power Outlet / Cigar Lighter
Wheel Type	7 x Single Piece Disc Rims (Including Spare)	Driving	Fuso Multimedia Unit Keyless Central Locking Electric Windows Cup Holders 2 3 seats
Wheel Size	17.5x6.0-127	Storage	Dual Overhead Storage Pockets In-Dash Centre Document Storage Door Storage Pockets Dash Storage Tray (1 DIN) Coat Hooks
Wheel Stud Pattern	6 Stud 222.25 PCD	Cab: External	Front End-Outline Marker Lamps Door Side Impact Beams
Tyre Type	Tube less	Chassis	Reverse Warning Buzzer Factory Reverse Camera with Infrared Display and Audible Pickup (Supply only in Cabin with Cab Chassis)
Tyre Size Front	215/75R17.5 124/123	Cab Features	
Tyre Size Rear	215/75R17.5 124/123	Type	All Steel Forward Control Manual Tilt
LUG Tyres Fitted (for Extra Traction)		Cab Structure	ECE-R29 European Cab Strength Approved
Spare Tyre Carrier	Provided	Mounting	Hydroelastic 4 Point
Chassis		Additional Engine Access	N/A
Type	Tapered Frame with Body Sub-frame	Colour	Natural White
Size	212x65x6mm	Windscreen Wipers	2 Speed + Intermittent Cycle with Integrated Washer Nozzles
Tensile Strength	540 MPa	Rear Vision Mirrors	1 x Internal 2 x External Convex (ECE 46) - Heated
Instruments		Seating Capacity	3
Gauges	Speedometer with Odometer Tachometer Fuel Level Water Temperature	Seat Belts	Lap Sash Belts for Outside Seating Positions Lap Belt for Centre Seat Driver Seat Belt Warning
Colour Information Display	Fuel Consumption DPF Bar Chart from 1~9 Water Temperature Maintenance Reminder System Tripmeters	Seat (driver)	Suspended with Weight Adjustment, LH Arm Rest and Lumbar Support
Multi-Media Package		Seats (passenger)	Flat Folding, 2 Passenger Bench
Satellite Navigation	GPS navigation specifically designed for commercial vehicle applications, with 3 years of Map updates included.	Service Intervals	
Colour Display	8" LCD with capacitive touch screen control	Interval*	30,000km or 12 Months (whichever occurs first)
Phone Connectivity	Wireless Apple Carplay & Android Auto Compatible	Warranty*	
Audio Visual Entertainment	Bluetooth® music streaming compatible Digital radio DAB+ (also AM/FM for areas not covered by DAB+) & USB	Basic/Powertrain	5 Years or 200,000kms (whichever occurs first)
Camera Compatibility	1 Reverse Camera fitted as standard Display can accept up to 5 additional cameras#	Notes	* Please refer to Fuso Owners Warranty Booklet for additional terms and conditions.
Notes	# Cameras available through spare parts	Performance	
		Turning Circle (kerb to kerb - metres)	10.4
		Road Speed (km/h) at Max Engine Speed	A 127 B 130
		Engine Speed (rpm) at 100km/hr (top gear)	A 2817 B 2687
		Gradeability at Rated GVM (theoretical)*	A 31% B 29%
		Notes	*This is theoretical performance only. Actual performance may vary under different conditions

# CANTER SPECIFICATIONS

## MODEL

<b>A</b>	4X2 815 WIDE CAB TIPPER SWB 6 SP. DUONIC AMT (FEC81CR3SFBG)
<b>B</b>	4X2 815 WIDE CAB TIPPER SWB 5 SP. MAN (FEC81CR4SFBG)

## WHEEL BASE

2800mm
2800mm

## GVM (optional)

7,500kg (4,495kg)
7,500kg (4,495kg)

## GCM (optional)

11,000kg (7,995kg)
11,000kg (7,995kg)

### Mass estimated\*


Front*	<b>A</b>	<b>B</b>
	1715kg	1705kg
Rear*		
	1550kg	
Total*	<b>A</b>	<b>B</b>
	3265kg	3255kg
Notes	* Mass (est.) includes oil and water but excludes spare wheel, tools & fuel. Weights provided are subject to 3.5% variation (+/-)	

### Dimensions mm

WFF (Width Front Fender) (mm)	1995
WRA (Width Rear Axle) (mm)	2144
WFT (Width Front Track) (mm)	1675
WRT (Width Rear Track) (mm)	1670
Width Frame (mm)	850
A - Length Overall (mm)	5415
C - Front Overhang (mm)	1140
D - Wheelbase (mm)	2800
G - Front Axle to Rear of Cab (mm)	525
P - Height Cab to Ground (mm)	2180
Q - Height Cab to Frame (mm)	1515
Tipper Body Width Outside	2255
Tipper Body Width Inside	2080
Tipper Body Length Inside	3400
Tipper Capacity (cubic metres)	2.6

### Built Ready

Features	<ul style="list-style-type: none"> <li>• Grab Handle and Step</li> <li>• Rope Rails</li> <li>• 3-way Tailgate</li> <li>• Dropdown sides gates</li> <li>• Slotted headboard</li> <li>• Hydraulic body lock</li> <li>• 60 degree tilt angle</li> </ul>
----------	--



**Call 1800 033 557**

or visit [fuso.com.au](http://fuso.com.au)

Unless specified in writing herein the accessories, applications, bodies or equipment depicted in this are for illustration purposes only and may not be available from Daimler Truck Australia Pacific Pty Ltd. ABN 86 618 413 282 DTAuP. No representation or warranty whatsoever is given in relation to any accessories, applications, bodies or equipment or suitability of same that are shown herein that may be manufactured, supplied or fitted by a party other than DTAuP. DTAuP reserves the right without notice or obligation to discontinue or make changes to the colour, designs, materials and specifications of the products and options referred to herein at any time. For the most current information and in order to ascertain which accessories, applications, bodies and equipment are available from DTAuP please contact your authorised FUSO dealer. Fuso is a registered trademark of Daimler Truck Australia Pacific Pty Ltd. Copyright DTAuP. Reproduction in whole or part prohibited without written approval. Valid from 01-Oct-24.